



GCS-039-SM7 THERMAL SILICONE GREASE

GCS-039-SM7 is a high performance silicone thermal grease

Features

- 3.9 W/m K thermal conductivity
- Easy to use
- High stability
- Excellent performance



Configurations

PART NUMBER	WEIGHT
GCS-039-SM7-20g	20g syringe
GCS-039-SM7-30g	30g syringe
GCS-039-SM7-1kg	1kg pot

Properties

CHARACTERISTIC	TEST METHOD	VALUE
Colour	Visual	Grey
Thermal Impedance °C-in2/W	ASTM D5470	<0.09
Thermal conductivity W/m K	ASTM D5470	3.9
Specific gravity. g/cm3	ASTM D1475	1.7
Dielectric constant	ASTM D150	>5
Operation temperature (°C)	-	-20 to +180
Viscosity (cps)	-	65,000

Applications

Displays, lighting protection: PDP TV, LCD CCFL and LCD LED display backlight, LED signage, projectors and new display technology.

Consumer and industrial electronics: Mobile telephone, communication base station, laptop, notebook, computer servers, handheld gaming devices, memory modules, CPU modules, amplifiers, batteries, and DC to DC converter power supplies.

Automotive electronics: Engine management, electronics suspension, braking systems, communication and multimedia systems, comfort convenience features, vehicle lighting, vehicle controls, hybrid vehicle battery thermal management, electric vehicle thermal management.



✉ info@gcsthermal.com

GCS UK Ltd

7 Priory Business Park
Kibworth, Leicestershire
LE8 0RX, UK